


# Cartridge Operated Type ABC Dry Powder and Monnex Powder Portable Fire Extinguishers



## FEATURES

- ✓ Fully deep drawn from cold rolled steel
- ✓ Externally coated with polyester powder
- ✓ Pressure tested to twice the extinguisher's working pressure



EED-4c

EED-6c

EED-9c

EED-12c

EED-12cMX

Model	EED-4c	EED-6c	EED-9c	EED-12c	EED-12cMX
Type	Cartridge Operated Type				
Extinguishant	ABC Dry Powder				Monnex Powder
Capacity	4 kg	6 kg	9 kg	12 kg	9 kg
CO <sub>2</sub> Gas Cartridge	75 g	110 g	150 g	225 g	225 g
Valve / Headcap	CE Marked Controllable Chrome Plated Brass Headcap with Safety Relief Valve				
Body Diameter	158 mm	158 mm	178 mm	188 mm	188 mm
Overall Height	480 mm	535 mm	595 mm	710 mm	710 mm
Approx Full Weight	7.9 kg	10.4 kg	14.1 kg	19.1 kg	16.1 kg
Working Temperature Range	-20°C to + 60°C				
Working Pressure	12 Bar				
Test Pressure	25 Bar				
Burst Pressure	Exceeds 69 Bar				
Approx Discharge Range	2-3 m	5 m	7 m	7 m	7 m
Approx Discharge Time	20 sec	20 sec	22 sec	31 sec	19 sec
Fire Rating	21A : 89B	27A:183B	34A:233B	43A:233B	233B
Fire Class	A, B, C + Electrical				B, C
Internal Coating	Stoving Epoxy Primer				
Paint Finishing	RAL 3000 Flame Red Epoxy Polyester Powder Coating				
Mounting	Metal 'T' Wall Bracket				
Manufactured & Certified to	BS EN 3-7: 2004 + A1: 2007, BS EN 3-8: 2006 and BS EN 3-10:2009				