


Cartridge Operated Type Water, Foam & Wet Chemical Portable Fire Extinguishers



FEATURES

- ✓ Fully deep drawn from cold rolled steel
- ✓ Externally coated with polyester powder
- ✓ Pressure tested to twice the extinguisher's working pressure



EEW-6cs

EEW-9cs

EEF-6cs

EEF-9cs

EEF-9c

EEK-6cs

EEK-9cs

Model	EEW-6cs	EEW-9cs	EEF-6cs	EEF-9cs	EEF-9c	EEK-6cs	EEK-9cs
Type	Cartridge Operated Type						
Extinguishant	Water		AFFF Foam (Premix)			Wet Chemical	
Capacity	6 litres	9 litres	6 litres	9 litres	9 litres	6 Litres	9 Litres
CO ₂ Gas Cartridge	55 g	55 g	55 g	75 g	75 g	35 g	55 g
Valve / Headcap	CE Marked Controllable Chrome Plated Brass Headcap with Safety Relief Valve						
Body Diameter	158 mm	178 mm	158 mm	178 mm	178 mm	158 mm	178 mm
Overall Height	585 mm	630 mm	585 mm	630 mm	630 mm	585 mm**	630 mm**
Approx Full Weight	11.1 kg	14.8 kg	11.1 kg	14.9 kg	14.9 kg	13.4 kg	18.7 kg
Working Temperature Range	+5°C to +60°C					0°C to 60°C	
Working Pressure	12 Bar						
Test Pressure	25 Bar						
Burst Pressure	Exceeds 69 Bar						
Approx Discharge Range	4 m	6 m	4 m	6 m	6 m	>2 Metres	
Approx Discharge Time	38 sec	49 sec	58 sec	88 sec	42 sec	70 sec	84 sec
Fire Rating	13A	21A	13A:144B	13A:183B	21A:183B	8A : 75F	13A : 75F
Fire Class	A + Electrical Safety Test*		A,B + Electrical Safety Test*		A,B	A,F + Electrical Safety Test*	
Internal Coating	Thermoplastic Powder Coating (PPA)						
Paint Finishing	RAL 3000 Flame Red Epoxy Polyester Powder Coating						
Mounting	Metal 'T' Wall Bracket						
Manufactured & Certified to	BS EN 3-7: 2004 + A1: 2007, BS EN 3-8: 2006 and BS EN 3-10:2009						

* Safe if in Accidental contact with Live Electrical Equipment. Complies with electrical Conductivity Test BS EN 3-7, Clause 9 Annex C.

** Overall height measure from bottom up to valve handle