


Stored Pressure Type Carbon Dioxide Portable Fire Extinguishers



KM 61549



0038



0098

FEATURES

✓ Seamless steel cylinder

✓ Externally coated with polyester powder



EEC-2e2

EEC-5e1

EEC-2Ale2

EEC-5Ale1

Model	EEC-2e2	EEC-5e1	EEC-2Ale2	EEC-5Ale1
Body Material	Cromoly Steel		Aluminium Alloy	
Extinguishant	Carbon Dioxide			
Capacity	2 kg	5 kg	2 kg	5 kg
Valve	CE Marked Controllable Chrome Plated Brass Valve			
Body Diameter	105 mm	138 mm	117 mm	152 mm
Overall Height*	567 mm	747 mm	502 mm	664 mm
Approx Full Weight	6.7 kg	15.0 kg	5.1 kg	12.1 kg
Working Temperature Range	- 20°C to + 60°C			
Working Pressure	56 bar			
Test Pressure	250 bar		212 bar	
Burst Pressure	180 - 200 bar			
Approx Discharge Range	3 m			
Approx Discharge Time	13 sec	23 sec	14 sec	18 sec
Fire Rating	34B	55B	34B	55B
Fire Class	B + Electrical			
Cylinder Specification	84 / 525 / EEC , BS 5045 Part 7, PED		BS 5045 Part 8 , PED	
Discharge Assembly	Swivel Horn	Hose & Fish Tail Horn	Swivel Horn	Hose & Fish Tail Horn
Paint Finishing	RAL 3000 Flame Red Epoxy Polyester Powder Coating			
Mounting	Metal 'L' Wall Bracket			
Manufactured & Certified to	BS EN 3-7: 2004 + A1: 2007, BS EN 3-9: 2006 and BS EN 3-10: 2009			

* Overall height measure from bottom upto valve handle